

SAFETY DATA SHEET RENDEROC SC

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME RENDEROC SC
SUPPLIER FOSROC Limited

Drayton Manor Business Park

Coleshill Road Tamworth Staffordshire B78 3TL

Tel. +44 (0) 1827 262222 Fax. +44 (0) 1827 262444

uk@fosroc.com

2 HAZARDS IDENTIFICATION

Risk of serious damage to eyes. Irritating to respiratory system and skin. May cause sensitisation by skin contact.

CLASSIFICATION Xi;R37/38, R41. R43.

ENVIRONMENT

In the presence of water the product hardens to a solid mass which is not biodegradable.

HUMAN HEALTH

Dust or splashes from the mixture may cause permanent eye damage. Dust may irritate throat and respiratory system and cause coughing. Dust has an irritating effect on moist skin. Prolonged contact with wet cement/mixture may cause burns. Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
ORDINARY PORTLAND CEMENT	266-043-4	65997-15-1	10-30%	Xi;R37/38,R41. R43.
GROUND GRANULATED BLASTFURNACE SLAG (GGBS)		65996-69-2	5-10%	Xi;R36/38.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move injured person into fresh air and keep person calm under observation. If uncomfortable: Seek hospital and bring these instructions.

INGESTION

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and take these instructions.

SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

EYE CONTACT

Do not rub eye. Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Continue flushing during transport to hospital. Bring these instructions.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use fire-extinguishing media appropriate for surrounding materials.

SPECIFIC HAZARDS

Water used for fire extinguishing, which has been in contact with the product, may be corrosive.

RENDEROC SC

PROTECTIVE MEASURES IN FIRE

Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Avoid inhalation of dust. Use work methods which minimize dust production. Avoid contact with eyes and prolonged skin contact. For personal protection, see section 8.

ENVIRONMENTAL PRECAUTIONS

The product should not be dumped in nature but collected and delivered according to agreement with the local authorities. Do not discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

For waste disposal, see section 13. Collect powder using special dust vacuum cleaner with particle filter or carefully sweep into closed container.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Observe good industrial hygiene practices. Avoid spread of dust. Avoid inhalation of dust. Avoid contact with eyes and prolonged skin contact. Avoid spread of dust. Mechanical ventilation may be required. Change contaminated clothing.

STORAGE PRECAUTIONS

To be stored out of reach of children in its original packaging in a dry place. The product contains less than 2 mg chromate/kg dry cement, and this limit will not be exceeded for 12 months from the packing date stated on the packaging. Seal opened containers and use up as soon as possible

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
ORDINARY PORTLAND CEMENT	WEL		4 mg/m3			
SILICA SAND (Silicon dioxide)	WEL		0,1 mg/m3			
SILICA SAND AFS 48	WEL		0,1 mg/m3			

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT







ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of dust.

RESPIRATORY EQUIPMENT

Dust mask/respirator.

Use respiratory equipment with particle filter, type P2.

(EN 149)

HAND PROTECTION

Wear protective gloves. PVC or rubber gloves are recommended. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. If signs of wear and tear are noticed then the gloves should be replaced.

EYE PROTECTION

Wear goggles/face shield. (conform EN 166)

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

RENDEROC SC

HYGIENE MEASURES

Change contaminated clothing. When using do not eat, drink or smoke.

PERSONAL PROTECTION

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. This product may present a chromate (VI) allergy risk. It contains a chromate reducing agent, but users should wear appropriate personal protective equipment.

ENVIRONMENTAL EXPOSURE CONTROLS

Not available

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Powder, dust

COLOUR Grey
ODOUR Odourless

SOLUBILITY Miscible with water.

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions. When stored under humid conditions, the chromate neutralization will decrease. This product contains a chromate reducing agent to reduce the risk of allergic dermatitis causes by chromium (VI). This product has a shelf life. If not stored in accordance with packaging instructions (sealed and dry), there is an increased risk of the presence of hexavalent chromate leading to an increased risk of an allergic reaction. The product will harden into a hard mass in contact with water and moisture.

CONDITIONS TO AVOID

Water, moisture.

MATERIALS TO AVOID

Strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

INHALATION

Dust may irritate throat and respiratory system and cause coughing.

INGESTION

Not likely, due to the form of the product. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.

SKIN CONTACT

Dust has an irritating effect on moist skin. Prolonged contact with wet cement/mixture may cause burns.

EYE CONTACT

Dust or splashes from the mixture may cause permanent eye damage. Immediate first aid is necessary.

SPECIFIC EFFECTS

Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product is not expected to be hazardous to the environment.

MOBILITY

The product is not volatile but may be spread by dust-raising handling.

DEGRADABILITY

The product is not biodegradable.

13 DISPOSAL CONSIDERATIONS

RENDEROC SC

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Note that fully cured material is not considered as hazardous waste.

WASTE CLASS

Waste from residues: 17-09-03

14 TRANSPORT INFORMATION

GENERAL The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA,

ADR/RID).

ROAD TRANSPORT NOTES Not Classified
RAIL TRANSPORT NOTES Not Classified.
SEA TRANSPORT NOTES Not Classified.
AIR TRANSPORT NOTES Not Classified.

15 REGULATORY INFORMATION

LABELLING



Irritant

CONTAINS ORDINARY PORTLAND CEMENT

RISK PHRASES

R37/38 Irritating to respiratory system and skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

SAFETY PHRASES

S2 Keep out of the reach of children
S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

S37/39 Wear suitable gloves and eye/face protection.

S46 If swallowed, seek medical advice immediately and show this container or label.

S51 Use only in well-ventilated areas.

S56 Dispose of this material and its container to hazardous or special waste collection point.

S64 If swallowed, rinse mouth with water (only if the person is conscious).

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

CHIP for everyone HSG(108).

NATIONAL REGULATIONS

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

RENDEROC SC

16 OTHER INFORMATION

GENERAL INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

REVISION DATE 26/11/2009

REV. NO./REPL. SDS GENERATED 5

RISK PHRASES IN FULL

R36/38 Irritating to eyes and skin.

R37/38 Irritating to respiratory system and skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

DISCLAIMER

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.