

Rev 2.0 - 20 December 2019

PRODUCT CODE - 203-RM

SECTION 1. Identification of the Substance/Mixture and of the Company/Undertaking

Product Identifier

- Mortars & plasters

NEWTON SYSTEM 200

- Product form
 Mixture
- Product name
 Newton 203-RM
- Product codes 203-RM

Relevant identified uses of the substance and uses advised against

- Use of substance/mixture
 Professional Use only Single component, polymer-modified, fibre-reinforced, Portland-based, fast setting repair mortar
- Uses advised against
 Not for any other use

Details of the Supplier of the Safety Data Sheet

- Company Address
 Newton Waterproofing Systems, Newton House, 17-20 Sovereign
 Way, Tonbridge, Kent TN9 1RH
- Web www.newtonwaterproofing.co.uk
- Email address of the competent person
- Emergency telephone numbers
 Newton Waterproofing systems English language +44 (0)1732 360095/08:00-17:30 (GMT) Mon-Thur & 08:00-17:00 (GMT) Fri

SECTION 2. Hazards Identification

Refer to SECTION 16 for

The explanation of the abbreviations used throughout this SDS The full list of Hazard Phrases & Precautionary Statements stated throughout this SDS

2.1 Classification of the Substance or Mixture

• Classification under Regulation (EC) No. 1272/2008 (CLP)

Skin Irrit, 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317
STOT SE 3	H335

• Adverse physicochemical, human health and environmental effects

See SECTION 11 for information on health effects and symptoms

2.2 Label Elements

- Signal words (CLP)
- Hazard pictograms (CLP)



- Hazard statements
- H318: Causes serious eye damage
- H317: Causes skin irritation
- H317: May cause an allergic skin reaction H335: May cause respiratory irritation

• Hazardous ingredients	Cement, Portland, chemicals Calcium aluminate sulphate
Precautionary statement: Pre	
General	To be handled and used in accordance with good occupational hygiene and safety practice. Wear PPE as SECTION 8.2, handle and store as SECTION 7, manage accidental release as SECTION 6 and follow the instructions in the Data Sheet
Prevention	P261: Avoid breathing dust/fume/gas/mist/vapours/spray
	P271: Use only outdoors or in a well ventilated area
	P280: Wear protective gloves/protective clothing/eye protection/face protection
Response	P302+P352: IF ON SKIN: Wash with plenty of soap and water
	P303+P361: IF ON SKIN (or hair): Immediately take off all contaminated +P353 clothing. Rinse skin with water / shower
	P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
	P305+P310: IF IN EYES: Immediately call a Poison Centre or doctor/ physician P363: Wash contaminated clothing before reuse
Storage	P403+P233: Store in a well-ventilated place. Keep container tightly closed
5	P405: Store locked up
Disposal	P501: Dispose of contents/container to local, national and international regulations
Supplemental label elements	NDA
2.3 Other Hazards	
Other Hazards	NDA
Other information	Classification and labelling have been made on the basis of safety data sheets of the raw materials that make up the product

SECTION 3. Composition/information on ingredients

3.2 Mixture

NEWTON SYSTEM 100 - MORTARS & PLASTERS

This product is a mixture

Hazardous Substances

Chemical name	CAS	EC No.	EC Index- No	REACH Registration Number	%	Classification according to Regulation (EC) No. 1272/2008 (CLP)
Crystalline silica	14808- 60-7	238- 878-4			≥50 - ≤75	Not classified
Cement, Portland, chemicals	65997- 15-1	266- 043-4			≥25 - ≤50	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Dam. 1, H318 STOT SE 3, H335
Calcium aluminate sulphate	12005- 25-3				≤3	Skin Sens. 1, H317 EUH066

NB

Refer to SECTION 8 for Occupational Exposure Limits & Controls and Personal Protection

Refer to SECTION 16 for the full text of Hazard Statements

There are no additional ingredients present, which, within the current knowledge of the supplier and in the concentrations applicable, are

(a trading name of John Newton & Co. Ltd.)

Newton House, 17-20 Sovereign Way, Tonbridge, Kent, TN9 1RH T: +44 (0)1732 360095 W: www.newtonwaterproofing.co.uk E: info@newtonwaterproofing.co.uk classified as hazardous to health or the environment, or are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this SECTION.

SECTION 4. First Aid Measures

4.1	4.1 Description of First Aid Measures				
٠	General	Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice. If exposed or concerned get medical advice / attention. If you feel unwell, seek medica advice			
		Those assisting the exposed persons to take no action involving personal risk or without training. Performing mouth-to-mouth can be dangerous, only to be done by trained personnel			
		Eye bathing equipment and First Aid Box should be available			
		Take this SDS with you when seeking medial advice			
•	Skin contact	Remove contaminated clothing. Gently remove all traces of product and wash with plenty of soap and water. Continue to rinse for at least 10 minutes. If skin irritation or rash occurs seek medial advice / attention. Do NOT use solvents or thinners			
•	Eye contact	Do not rub. Immediately rinse eyes cautiously with plenty of water for at least 15 minutes holding the eyelids open. Remove contact lenses if present and easy to do so, then continue to rinse copiously for 15 minutes. Obtain immediate medical attention			
•	Ingestion	If swallowed, seek medical advice immediately and show the container or label and this SDS. Keep person warm and at rest. Do NOT induce vomiting. If vomiting occurs, the head should be kept forward and low so vomit does not enter the lungs. Never give anything to an unconscious person. Move the exposed person to fresh air. If unconscious, place in the recovery position and get medical advice immediately. Loosen tight clothing such as collar, tie, belt and waistband. Seek medical advice if you feel unwell			
•	Inhalation	Immediately ventilate the area and remove person from the contaminated place to rest in fresh air and keep comfortable and breathing. Assure fresh air breathing. Loosen tight clothing such as collar, tie, belt or waistband. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If you feel unwell seek medical advice			
•	Self-protection for first aiders	No action to be taken involving any personal risk or without suitable training. If it is suspected that the mixture is still present, wear appropriate Personal Protection Equipment, see SECTION 8.2. Wear gloves to remove contaminated clothing, see SECTION 13 for washing or disposal			

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Potential acute health effects:

٠	Skin contact	Causes skin irritation. May cause an allergic reaction
٠	Eye contact	Causes serious eye damage
٠	Ingestion	Irritating to mouth, throat and stomach
٠	Inhalation	May cause respiratory irritation
٠	Delayed / immediate effects	NDA
0	ver-exposure signs / symptoms:	
٠	Skin contact	Adverse symptoms may include pain or irritation, redness, blistering
•	Eye contact	Adverse symptoms may include pain, watering, redness

- ngestion Adverse symptoms may include stomach pains
- Ingestion

NEWTON SYSTEM 100 - MORTARS & PLASTERS

Page 3 of 14

(a trading name of John Newton & Co. Ltd.)

Newton House, 17-20 Sovereign Way, Tonbridge, Kent, TN9 1RH T: +44 (0)1732 360095 W: www.newtonwaterproofing.co.uk E: info@newtonwaterproofing.co.uk

Inhalation	Adverse symptoms may include respiratory tract irritation, coughing
• Delayed / immediate effects	NDA
4.3 Indication of Any Immediate Medic	al Attention and Special Treatment Needed
• Immediate / special treatment	No specific treatment. Treat symptomatically. Contact poison centre immediately if large quantities have been ingested or inhaled
SECTION 5. Fire-Fighting Mea	sures
5.1 Extinguishing Media	Use an extinguishing agent suitable for the surrounding fire
	Unsuitable extinguishing media: - None known
5.2 Special Hazards Arising from the M	laterial
	No specific fire or explosion hazard
5.3 Hazardous thermal decomposition	products
	Decomposition products may include Carbon dioxide, carbon monoxide, sulphur oxides, metal oxide / oxides
5.4 Advice for Firefighters	Isolate the affected area
	All persons to be immediately removed from the vicinity of the fire. Fire to be dealt with by trained personnel and without involving personal risk
	Exercise caution when fighting any chemical fire
	Collect the fire fighting water separately. Prevent from entering the environment, waterways, sewers and drains, alert the Environmental Agency if this occurs
	Do not enter the area without wearing appropriate protective equipment and self-contained breathing apparatus (SCBA) with full face-piece operated in positive pressure mode. Clothing, including helmets, protective boots and gloves, conforming to EN 469 will provide a basic level of protection for chemical incidents
SECTION 6. Accidental Release	e Measures
6.1 Personal Precautions, Protective Eq	uipment and Emergency Procedures
General measures	Do not attempt to take action without wearing suitable personal protection,

refer to SECTION 8.2 of the SDS Ensure adequate ventilation Non-emergency personnel Evacuate unnecessary personnel and keep unnecessary and unprotected personnel from entering No action is to be taken involving personal risk or without suitable training. Do not touch or walk through the spilled material. Ventilate spillage area. Wear appropriate face mask when ventilation is inadequate and PPE as SECTION 8.2. Do not breathe dust / fumes/ gas / vapours / mist / spray. Avoid contact with skin and eyes Emergency personnel Evacuate unnecessary personnel and those not wearing the suitable protection. If outside do not approach from downwind. If outside keep bystanders and passing persons upwind and away from the danger point. Mark out the contaminated area with signage and prevent access by unauthorised persons Do not attempt to take action without suitable protective equipment. Equip clean-up crew with proper protection, see SECTION 8 'Exposure controls / personal protection' Ensure adequate ventilation, including forced ventilation if in an internal

Page 4 of 14

persons and the general public Turn leaking containers leak-side up to prevent the escape of material, and place in a sealable leak proof container, label this with the contents Avoid inhalation of vapours, wear respiratory protection as SECTION 8.2 **6.2 Environmental Precautions** Prevent the product from contact with soil and from entering drains, sewers, watercourses, basements or confined spaces (refer to SECTION 11). Contain the spillage using bunding Alert the Environmental Agency in the event of spillage, etc. entering water ways, sewers or drains 6.3 Methods and Materials for Containment and Cleaning Up Clean-up should ONLY be dealt with by gualified persons familiar with the specific product. Approach from upwind against dust inhalation Stop the leak if it is safe to do so. Avoid dust generation Large spillages should be contained by bunding using absorbent materials and carefully transferred into sealable impervious containers. Remnants from large spillages and small spillages should be carefully swept up without dust generation and transferred into these containers. Using a vacuum with a HEPA filter will reduce dust dispersal All collected spillages to be retained within and fully collected up into sealable impervious waste container(s), label these with the contents If used, all contaminated bunding, including all suspected of being contaminated, to be collected up and transferred to these waste containers All containers to be labelled and held for disposal as SECTION 13 6.4 Reference to Other Sections Refer to SECTIONS 1 (Emergency contact), 8 (Personal Protection / Exposure Controls), 12 (Ecological Information) and 13 (Disposal Consideration)

space and necessary, and vent externally to be safely away from other

SECTION 7. Handling and Storage

The information in the SECTION includes generic advice and guidance. The list of 'Relevant identified uses' in SECTION 1 should be consulted for any available use-specific information provided here and in SECTION 8

7.1 Precautions for Safe Handling

NEWTON SYSTEM 100 - MORTARS & PLASTERS

	5	
a.	Safe handling	Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product
		Wear protective equipment as required by use- see SECTION 8
		Do not get in eyes, on skin or on clothing - see SECTION 8 for the protection of work clothing. Do not ingest. Obtain special instructions before use. Do not handle or use until all safety precautions have been read and understood.
		Only use outdoors or in well ventilated areas, wear appropriate respirator when ventilation is inadequate. Keep in original container, kept tightly closed when not in use
		Do not breathe vapours, aerosols or gases
b.	Hygiene measures	Do not eat, drink or smoke when handling. Wash hands and other exposed areas with mild soap and water after using the material and remove contaminated clothing and protective equipment before entering areas where food and drink are consumed and when leaving the work site. Wash hands and face before eating, drinking, smoking and using the toilet
		Wash hands and face before eating, drinking, smoking and using the toilet Contaminated work clothing should be securely bagged before being allowed out of the work site. See SECTION 13 for the protection of work clothing and the washing or disposal of contaminated work clothing and boots

Page 6 of 14

C.	Prevention of handling incompatible	e substances or mixtures
		Do not handle other substances or mixtures at the same time. Keep away from other substances and mixtures
d.	Operations and conditions that could	d create new risks
		Do not allow opened, part used or the container in use to come into contact with other materials including all surfaces around. Ensure the containers are securely sealed during transport, storage and when at the work site
e.	Reduce risk of release to the enviror	nment
		Avoid spillage. Ensure the floor at storage, transport and the work location will not allow access to drains or water courses. Lay heavy gauge plastic sheeting or similarly impervious protective covering when mixing and dispensing. Contain and clean up spillage as SECTION 6.3 of the SDS
7.2	Conditions for Safe Storage, Includi	ng Any Incompatibilities
a.	Storage conditions	Store in a well ventilated locked area, keep cool, away from direct sunlight and in accordance with local regulations. Only store in original containers. Keep container tightly closed. Do not store in unlabelled containers, if transferred to another container include the Batch Number and Manufacturing or Expiry Date on the new label. The floor of the storage area to be impermeable to prevent the escape of spillage
b.	Maximum storage period	Maximum storage / use period: 12 months at 20°C (68°F), refer to the container label for the Date of Manufacture, Expiry Date or Best Before Date
		Use of the stock must be by date rotation, using the oldest dates first. Containers past their expiry date must be removed for disposal according to SECTION 13 of the SDS
C.	Control of the effects of weather, an	bient pressure, temperature, sunlight, humidity and vibration
		Protect from freezing, frost, heat and direct sunlight. Keep away from sources of ignition, open flames or excessive heat
		Ensure containers are securely closed against vibration spillage during transport when loading / unloading vehicles, during transport and moving from vehicle to the work location. Unopened containers to be protected against damage during these movements
d.	Storage with other substances and r	nixtures
		Only store in the original packaging. Store against falling / touching other materials and in an allocated location
e.	Storage room design, quantity limits	s, ventilation and packaging compatibilities
		Storage room to be dry, ventilated, and constructed to have impermeable floors and walls to prevent the escape of spillages into the environment
f.	Other considerations	No other data available
7.3	Specific End Use(es)	Single component, polymer-modified, fibre-reinforced, Portland-based, fast-setting repair mortar. Refer to the Technical Data Sheet for further information

SECTION 8. Personal Protection/Exposure Control

The information in this SECTION contains generic advice and guidance and is based on typical anticipated uses of the product. Additional measures might be required for bulk handling or uses other than those described in the Technical Data Sheet that could significantly increase worker exposure or environmental releases

8.1 Control Parameters

Workplace Exposure Limits (WEL)

EH40: Taken from the HSE EH40/2005 (3rd edition, published 2018): - not stated = not on EH40 - if no 15 min STEL, 3x TWA used Carc: Capable of causing cancer and / or heritable genetic damage Sen: Capable of causing occupational asthma

- Sk: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systematic toxicity
- Substance Long-term exposure Short-term exposure Comments Source & limit (8hr TWA limit (15 minute CAS reference period) reference period) mg / m³ mq / m^3 The Carc, Sen and Sk notations ppm ppm are not exhaustive. Notations have been applied to substances identified in IOELV Directives Crystalline silica - respirable 14808-60-7 EH40 0.1 Cement, Portland, chemicals - respirable & inhalable dust 65997-15-1 Inhal 10 EH40 **Respir 4** Calcium aluminate sulphate 12005-25-3 EH40 Not listed on the EH40 Recommended monitoring procedures Reference should be made to monitoring standards, such as: EN 689 Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and

measurement strategy EN 14042 Workplace atmospheres - Guide for the application and use for the assessment of exposure to chemical and biological agents

EN 482 Workplace atmospheres - General requirement for the performance of procedures for the measurement of chemical agents

Reference to national guidance documents for methods for the determination of hazardous substances will also be required

Only use with adequate ventilation. If user operations generates dust, fumes, gas, vapour or mist, use process enclosures, ensure there is sufficient ventilation in the area including forced ventilation if necessary or in an internal or enclosed space, all with safe exhaust away from other persons. The floor must be impermeable to prevent the escape of material, laying

Isolate the work area with warning signage against unauthorised access.

Ensure all other persons are pre-notified of the works and remain clear of

Provide eye wash facilities, individual eye wash ampoules and safety shower

When opening the container and when progressively mixing with water When using the power mixer / paddle off a drill, include erecting barrier around if necessary to stop splashes off the protective sheeting onto

Refer to SECTION 15.1 for any 'Other Regulations' and the REACH Annex

Only mix the product with the required amount of water on impervious protective sheeting and with this laid at the area(s) where the mixed product is to be applied, against splashes onto the person(s) performing this task,

DNELs / DMELs

No DNELs / DMELs available

impermeable protective covering if in doubt

any other persons and onto the surrounding areas:

No PNECs available

the work area

XVII statements there

PNECs

NEWTON SYSTEM 100 - MORTARS & PLASTERS

8.2 Exposure Controls

8.2.1 Appropriate Engineering Controls

a. Ventilation

b. Isolation

c. Washing

d. Against contamination

Page 7 of 1⁴

NEWTON SYSTEM 100 - MORTARS & PLASTERS

		other persons, structures, ground, etc
		 When applying the mixed product to the area(s) to be treated
		• The person(s) performing this to wear disposable overshoes over their safety work boots when working off the protective sheeting against walking contamination onto the surrounding area
		 When the mixing is done, dispose of the contaminated protective sheeting, the overshoes, etc as controlled waste
e.	Mists	Prevent the formation of vapour or aerosol
f.	Hygiene & Occupational care	Do not eat, drink or smoke during stirring or use of the product. Wash hands, face and uncovered forearms with soap and water before eating, drinking, smoking, using the toilet and when leaving the work site for natural breaks, break times and at end of day
8.2	.2 Personal Protective Equipment	
a.	Work clothing	Wash contaminated work clothing before reusing. Alternatively wear impervious disposable 1-piece covering to body, legs and arms with closure at wrists and ankles, and disposable overshoes. EN ISO 13688
b.	Eye / face protection	Tight fitting safety chemical goggles / safety glasses with side protection or face visor, to EN166
		If at risk of splashing to face when mixing the product with water wear a full face visor
C.	Skin protection (i) Hand Protection	To be impermeable chemical resistant gloves, resistant to micro-organisms, to EN 374
	Material of gloves	The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC, this being repealed by EU 2016/425 on 21/04/2018, and the resultant standard EN 374
		Recommended: Butyl rubber gloves. The selection of the suitable gloves does not only depend upon the material, but also further marks of quality and varies from manufacturer to manufacturer
		Break through, and other characteristics, depending upon material density and the glove type, and must be determined in each case
		Gloves to be tightly fitting at the wrists and extend onto the work clothing, see above. Gloves must be inspected prior to each time used and must be replaced when damaged or worn out
		Impervious gloves, chemical resistant: Vitron ${ m I\!R}$ or Nitrile to EN 374
	Penetration time of gloves	Breakthrough time of the glove material - prolonged use > 8 hours
		- brief contact > 30 minutes
(ii)	Other	Chemical resistant safety boots with external feed for the laces, not holes for the laces
		Barrier creams may help to protect exposed skin areas but should not be applied once exposure has occurred
		Safety helmet if required, or other head covering, against splashes
		Good hygiene measures should be followed at all time
d.	Respiratory protection	Mouth & nose filter face mask to EN149:2001, with Face Fit Certification
		In the case of inadequate ventilation wear an appropriate gas filter (e.g. type A according to EN 14387). Ensure the filter is within its working limits
		Mist formation; wear protection as for inadequate ventilation
e.	Thermal hazards	NDA
f.	Environmental exposure measures	Avoid release to the environment
		Emissions from ventilation or work process equipment should be checked

to ensure they comply with the requirements of environmental legislation. Apply process engineering modifications, ventilation filters, etc. if required

SECTION 9. Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

٠	Appearance	(i) Form	Solid (powder)
		(ii) Colour	Grey
٠	Odour		Odourless
٠	Odour threshold		NDA
٠	рН		NDA
•	Melting point/rar	nge °C	NDA
٠	Freezing point/ra	nge °C	NDA
•	Initial boiling poi	nt/range °C	NDA
•	Flash point/self-ig	gnition °C	Closed cup: 101°C
•	Evaporation rate		NDA
٠	Flammability (sol	id, gas)	NDA
•	Flammability limi	ts, lower %	NDA
•	Flammability limi	ts, upper %	NDA
•	Auto flammability	∕ °C	NDA
•	Decomposition te	emperature	NDA
٠	Explosive propert	ties	NDA
٠	Explosive limits		NDA
٠	Oxidising proper	ties	NDA
٠	Vapour pressure		NDA
٠	Relative vapour d	ensity at 20°C	NDA
٠	Relative density		2.62
٠	Specific weight		NDA
٠	Solubility in wate	r	Soluble in cold water
٠	Partition coefficie	nt n-octanol/water	NDA
٠	Also soluble in		NDA
٠	Viscosity, kinema	tic	999.1 mm ² /s (room temperature)
٠	Viscosity, dynami	С	NDA
٠	VOC g/l		NDA
NC	DTE:		The above values related to physiochemical properties are typical values for this product and should not, therefore, be construed as a specification
9.2	2 Other Informatio	n	NDA

SECTION 10. Stability and Reactivity

NEWTON SYSTEM 100 - MORTARS & PLASTERS

10.1 ReactivityNo specific test data related to reactivity is available for this product or its
ingredients10.2 Chemical StabilityStable at room temperature, under recommended transport or storage
conditions and when protected against the materials or conditions listed in
SECTIONS 10.1 and 10.3

10.3 Possibility of Hazardous Reactions	Under normal conditions of storage and use (see the Technical Data Sheet), hazardous reactions will not occur	
10.4 Conditions to Avoid	No specific data	
10.5 Incompatible Materials to Avoid	No specific data	
10.6 Hazardous Decomposition Products	Under normal conditions of storage and use, hazardous decomposition products should not be produced	
SECTION 11. Toxicological Information		

11.1 Information on Toxicological Effects

Acute toxicity

Harmful if inhaled

In the absence of experimental toxicological data on the product itself, the potential risks to health were evaluated based on the properties of the constituent substances, according to the criteria laid down by the relevant regulations for Classification

Hazardous ingredients

- Conclusion: NDA

Irritation / Corrosion - Hazardous ingredients

- Conclusion: NDA

Specific target organ toxicity - single exposure (STOT SE)

Substance	Category	Route of exposure	Target organs
Cement, Portland, chemicals	Category 3	Not applicable	Respiratory tract irritation

Other hazards

NEWTON SYSTEM 100 - MORTARS & PLASTERS

Hazard	Negative Symptoms
Respiratory hazard / inhalation	May cause respiratory irritation if inhaled
Serious eye damage / irritation	Causes serious eye damage
Skin sensitisation	May cause an allergic skin reaction
Skin corrosion / irritation	Causes skin irritation
Ingestion	Irritating to mouth, throat and stomach
STOT single exposure	May cause respiratory irritation

Hazard	Basis
Acute toxicity - oral	NDA
Acute toxicity - dermal	NDA
Acute toxicity - inhalation	NDA
Skin sensitisation	NDA
Skin corrosion / irritation	NDA
Carcinogenicity	NDA
Germ cell mutagenicity	NDA
Reproductive toxicity	NDA
Teratogenicity	NDA
Aspiration hazard	NDA
STOT repeated exposure	NDA
· ·	

Viscosity, kinematic

999.1 mm²/s

Information on likely routes of exposure NDA

Symptoms related to the physical chemical and toxicological characteristics

•	Symptoms related to the physical, cl	nemical and toxicologic	cal characteristics
		Inhalation - Adv	erse symptoms amy include pain, watering, redness erse symptoms may include respiratory tract irritation, ughing
		Skin contact - Adv	erse symptoms may include pain or irritation, redness, istering may occur
		Ingestion - Adv	erse symptoms may include stomach pains
•	Delayed and immediate effects as w	ell as chronic effects fr	om short and long-term exposure
	Short-term exposure	Potential immediate e Potential delayed effe	
	Long-term exposure	Potential immediate e Potential delayed effe	
	Potential chronic health effects	NDA	
	Conclusion	NDA	
		General	 Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels
		Carcinogenicity Mutagenicity Teratogenicity Developmental effects Fertility effects	 No known significant effects of critical hazard No known significant effects of critical hazard No known significant effects of critical hazard No known significant effects of critical hazards No known significant effects of critical hazards
•	Other information	NDA	
		manufacturer's SDS w	ested. The data reported here are based on the hich is based on information contained in the safety materials that make up the product

SECTION 12. Ecological Information

NEWTON SYSTEM 100 - MORTARS & PLASTERS

12.1 Toxicity	NDA
12.2 Persistence and Biodegradability	NDA
12.3 Bioaccumulative Potential	NDA
12.4 Mobility in Soil	NDA
12.5 Results of PBT & vPvT Assessmen	t N/A
12.6 Other Adverse Effects	No known significant effects or critical hazards
12.7 Additional information	The product was not tested. The data reported here are based on the manufacturer's SDS which is based on information contained in the safety data sheets of the raw materials that make up the product
	No other information available

SECTION 13. Disposal Considerations

13.1 Waste Treatment Methods

- Recovery operations Treat as SECTION 6: Accidental Release Measures
 Disposal operations Product dispose at approved waste collection sites as controlled waste
 Disposal of packaging Paper bag always has remnants, dispose of a controlled waste
 Waste code number Wet & solidified mixed (with water) product: 17 01 06* Packaging: 15 01 10*
- Special precautions for the disposal method

Ensure substances or mixtures are not mixed with other materials and if

© Newton Waterproofing Systems (a trading name of John Newton & Co. Ltd.) Newton House, 17-20 Sovereign Way, Tonbridge, Kent, TN9 1RH T: +44 (0)1732 360095 W: www.newtonwaterproofing.co.uk E: info@newtonwaterproofing.co.uk

held in the same outer container with other materials all are in separate sealed containers within the outer container

• NB

NEWTON SYSTEM 100 - MORTARS & PLASTERS

The user's attention is drawn to the possible existence of regional or national regulations regarding disposal

SECTION 14. Transport Information

ADR	IMDG		IATA	ADN	RID
14.1 UN Number			•		-
Not regulated	Not regula	ted	Not regulated	N/A	Not regulated
14.2 UN proper shippir	ng name				
N/A	N/A		N/A	N/A	N/A
14.3 Transport hazard o	class(es)				
N/A	N/A		N/A	N/A	N/A
14.4 Packing group					
N/A	N/A		N/A	N/A	N/A
14.5 Environmental haz	zards				
No	No		No	N/A	No
No supplementary info	ormation availab	le			
4.6 Special Precaution	s for User	that pe	transport in closed cor rsons transporting the it or spillage		
Overland transport N/A		N/A			
Transport by sea		N/A			
Air transport		N/A			
Inland waterway tra	nsport	N/A			
Rail transport		N/A			
4.7 Transport in Bulk A	According to:	Transpo	ort in bulk is not availa	able / offered	
(i) Annex II of Mai	_	N/A		-	
(ii) the IBC Code	1	N/A			

SECTION 15. Regulatory Information

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance, Mixture or Article

COMMISSION REGULATIONS (EC) No 1272/2008 and (EU) No 2015/830 of 28/05/2015 amending Regulation (EC) No 1907/2006 and repealing (EU) 453/2010 20 May 2010 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

Other regulations, limitations and prohibitive regulations

Contains no REACH substances with Annex XVII restrictions Contains no REACH Annex XIV substances

15.2 Chemical Safety Assessment

A chemical safety assessment has not been carried out. Data from the component substances is included in this SDS

Newton House, 17-20 Sovereign Way, Tonbridge, Kent, TN9 1RH T: +44 (0)1732 360095 W: www.newtonwaterproofing.co.uk E: info@newtonwaterproofing.co.uk

SECTION 16. Other Information

16.1 Basis of this SDS

The data reported here are based on the manufacturer's SDS which is based on information contained in the safety data sheets of the raw materials that make up the product

16.2 Changes Compared to the Previous Version

Date	Replaces	Sections	Item	Change	Comment
20/12/19	1.0	All	All	See comment	Full re-write, read the entire document
.6.3 Key lite	erature and	sources of	data Regulation (EC) 1907/2006 Regulation (EC) No. 1272/200 Regulation (EU) No. 2015/83 Supplier SDS ECHA, including REACH doss EH40/2005 3rd Edition, 2018	0	nent substances
.6.4 Abbrev	viations & A	Acronyms	CLP: EU Regulation 1272/20 chemical substances		on, Labelling & packaging of
			DMEL: Derived Minimal Effec		
			DNEL: Derived No Effect Leve		
			EINECS: European Inventory European List of Not		nmercial Chemical Substances of Substances of Substance number
			EUH statement: CLP-specific		nent
			HSE: (UK) Health & Safety Ex	ecutive	
			N/A: Not Applicable		
			NDA: No Data Available		
			PBT: Persistent, Bioaccumulat		
			vPvB: Very Persistent and ver	<i>,</i>	itive substances
			PNEC: Predicted No-Effect Co		
			REACH: Registration, Evaluati Chemicals: Regulation (EC) N		ion and Restriction of
			SDS: Safety Data Sheet		
			STEL: Short Term Exposure Li	mit	
			STOT RE: Specific target orga		
			STOT SE: Specific target orga	· · ·	n) single exposure
			TWA: Time Weighted Averag		
			VOC: Volatile organic compo	unds	

16.5 Procedure used to derive the Classification according to Regulation (EC) No. 1272/2008

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
STOT SE 3, H335	Calculation method

16.6 Full text of H and EUH statements

H315	Causes skin irritation	
H317	May cause an allergic reaction	
H318	Causes serious eye damage	
H335	May cause respiratory irritation	

16.7 Full text of Classifications (CL	P / GHS)
---------------------------------------	----------

EUH066	Repeated exposure may cause skin dryness or cracking
Eye Dam. 1, H318	Serious Eye Damage / Eye Irritation - Category 1
Skin Irrit. 2, H315	Skin Corrosion / Irritation - Category 2
Skin Sens. 1, H317	Skin Sensitisation - Category 1
STOT SE 3, H335	Specific Target Organ Toxicity - Category 3
16.8 Training advice	Obtain special instructions and read the Safety Data Sheet before use. Do not handle until all safety precautions have been read and understood. It is recommended that workers are trained in the safe handling of hazardous

16.9 DISCLAIMER

Persons using the information contained here must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where these purposes are other than as specifically recommended in this Safety Data Sheet and in the Technical Data Sheet, then the user uses the product at their own risk

chemicals

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best on the Company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to is accuracy, reliability or completeness. It is the users responsibility to satisfy themselves as to the suitability of such information for their own particular use