Technical Support: 0333 202 6800 **LAST UPDATED: 11.11.2015**



ECO Temporary Protective Sheeting

Page 1



















NSSPlus

- 100% Recycled LDPE
- Available in light duty, medium duty, heavy-duty and extra heavy-duty grades
- Supplied in convenient sized rolls
- Can be used for a variety of applications including environmental protection such as dust and rain

Description

 ϵ

Visqueen Building Products ECO TPS range is a blown film of extruded low-density polyethylene. Visqueen ECO TPS range is a high quality Temporary Protective Sheeting (TPS) manufactured from 100% Recycled LDPE. ECO TPS is available in 4 different sizes and can be used for a wide variety of applications. Visqueen Building Products ECO TPS enables users to protect worksites whilst doing more to protect the environment. ECO TPS is a range of temporary protective sheeting for use on floors, verticals, fixtures and fittings that's made entirely from recycled waste polythene - predominantly from the UK's agricultural and horticultural industries.

Application

Visqueen ECO TPS range is a temporary high performance protection material used to protect flooring, vertical, fixtures and fittings from the effects of dust. It is also durable, and helps contain dirt and any spillages. ECO TPS is easy to tailor fit as it only needs to be cut into shape.

Visqueen double sided jointing tape and Girth tape can be used for successful joining of Visqueen protective materials.

General Information

Visqueen ECO TPS film is available in manageable roll sizes which is labour saving and covers large areas fast, so less jointing has to take place. The ease of fit helps speed up the protection process, reducing the risk of damage to exposed finishes.

Bespoke sizes

These are available on request and are subject to a minimum order quantity. Please contact us enquiries@visqueenbuilding.com for further information

Installation

Preparation

To ensure the highest performance of the material, TPS protection should be installed as soon as all surfaces or fixtures are clean.

Cut and Fit

Unroll the material and cut to fit the area which is going to be protected. Allow an overlap of at least 150mm to provide a dust free joint when taped securely











Technical Support: 0333 202 6800 **LAST UPDATED: 11.11.2015**



ECO Temporary Protective Sheeting

Appendix A







Visqueen Building Products

Visqueen is the market leader in the manufacture and supply of structural waterproofing and gas protection systems. Visqueen offers the complete package - a proven, reliable range backed by a technical support service that goes unmatched in the market - everything you would expect from a reputable and ethical company.

System Accessories

To ensure full waterproofing protection please use the following certified system components:

- Visqueen High Performance (HP) Tanking Primer
- Visqueen TreadGUARD1500
- Visqueen Protect&Drain
- Visqueen Top Hat Unit

Downloads Library

- · Technical Datasheet
- Declaration of Performance
- · Visqueen's Guide to CE Marking

Find your local stockist

Search our directory of Visqueen specification Stocking Centres to locate your nearest Visqueen Partner.

Distributor Support

Our specification Stocking Centres can access a free library of sales support tools, bespoke catalogues and more, click here.

Technical support throughout your project

We are specialists in our field and can help you specify the correct solutions with the necessary performance levels, in accordance with building regulations.

- · Nationwide site support team
- · Specification advice
- Installation guidance & project sign off
- · System design including CAD details

















