

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	ARDEX DPM 1 C PART A
PRODUCT NO.	BADPM1C10, BADPM1C25, BADPM1C6
SUPPLIER	Ardex UK Limited Homefield Road Haverhill Suffolk CB9 8QP Tel. 01440 714939 Fax. 01440 716667 e-mail: safetydatasheets@ardex.co.uk
EMERGENCY TELEPHONE	+44 (0) 870 190 6777 (24 hours)

2 HAZARDS IDENTIFICATION

May cause sensitisation by skin contact. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. CLASSIFICATION (1999/45)

Xi;R36/38. R43. N;R51/53.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
Air release agent		64742-47-8	1-5%	Xn;R65.
epoxy resin		55492-52-9	10-30%	Xi;R36/38. N;R51/53. R43.
EPOXY RESIN (Number average MW <= 700)	500-033-5	25068-38-6	10-30%	R43 Xi;R36/38 N;R51/53
LEVELLING ADDITIVE			1-5%	Xn;R65. Xi;R36/37. N;R51/53. R10.
N-METHYL-2-PYRROLIDONE	212-828-1	872-50-4	< 1%	Xi;R36/38
OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS		68609-97-2	5-10%	R43 Xi;R38
Polyether modified trisiloxane		134180-76-0	1-5%	Xn;R20. Xi;R36. R52/53.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues. INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

ARDEX DPM 1 C PART A

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Avoid discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS

Chemical storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA	- 8 hrs	STEL	- 15 min	Notes
N-METHYL-2-PYRROLIDONE	WEL	25 ppm(Sk)	103	75 ppm(Sk)	309	
			mg/m3(Sk)		mg/m3(Sk)	

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HAND PROTECTION

Use protective gloves made of: Nitrile. Viton rubber (fluor rubber). Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

Wear tight-fitting goggles or face shield.

OTHER PROTECTION

EYE PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
COLOUR	Green Red
ODOUR	Characteristic
SOLUBILITY	Immiscible with water

10 STABILITY AND REACTIVITY

REVISION DATE: 15/11/2010

ARDEX DPM 1 C PART A

STABILITY Stable under normal temperature conditions. CONDITIONS TO AVOID Avoid excessive heat for prolonged periods of time. HAZARDOUS POLYMERISATION Will not polymerise. MATERIALS TO AVOID Strong oxidising substances. HAZARDOUS DECOMPOSITION PRODUCTS Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

INHALATION Irritating to respiratory system. INGESTION May cause stomach pain or vomiting. SKIN CONTACT May cause sensitisation by skin contact. Irritating to skin. EYE CONTACT Irritating to eyes.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



UK ROAD CLASS	9		
PROPER SHIPPING NAME	ENVIRONMENTALLY HAZA MW <= 700), epoxy resin)	RDOUS SUBSTANCE, LIQUID, N.O	.S. (EPOXY RESIN (Number average
UN NO. ROAD	3082	UK ROAD PACK GR.	III
ADR CLASS NO.	9	ADR CLASS	Class 9: Miscellaneous dangerous substances and articles.
ADR PACK GROUP	III	HAZARD No. (ADR)	90
ADR LABEL NO.	9	HAZCHEM CODE	3Z
CEFIC TEC(R) NO.	90GM6-III	RID CLASS NO.	9
RID PACK GROUP	III	UN NO. SEA	3082
IMDG CLASS	9	IMDG PACK GR.	III
EMS	F-A, S-F	MFAG	See Guide
MARINE POLLUTANT	No.	UN NO. AIR	3082
AIR CLASS	9	AIR PACK GR.	111

15 REGULATORY INFORMATION

LABELLING





Dangerous for the

	imiani	environment	
CONTAINS	epoxy resin		
	EPOXY RESIN (Nu	umber average MW <= 700)	
	OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS		
RISK PHRASES			
	R43	May cause sensitisation by skin contact.	
	R36/38	Irritating to eyes and skin.	
	R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.	
SAFETY PHRASES			
	S37	Wear suitable gloves.	
	S24/25	Avoid contact with skin and eyes.	
	S60	This material and its container must be disposed of as hazardous waste.	
	S61	Avoid release to the environment. Refer to special instructions/safety data sheets.	
	P5	Contains epoxy constituents. See information supplied by the manufacturer.	

STATUTORY INSTRUMENTS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply. GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

REVISION DATE 15/11/2010

REV. NO./REPL. SDS GENERATED 3

RISK PHRASES IN FULL	
R10	Flammable.
R20	Harmful by inhalation.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R36/37	Irritating to eyes and respiratory system.
R36/38	Irritating to eyes and skin.
R36	Irritating to eyes.
R38	Irritating to skin.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.