



## SAFETY DATA SHEET COLPOR 200PF BASE

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**PRODUCT NO.** M1139061

**SUPPLIER** FOSROC Limited  
Drayton Manor Business Park  
Coleshill Road  
Tamworth  
Staffordshire  
B78 3TL  
Tel. +44 (0) 1827 262222  
Fax. +44 (0) 1827 262444  
enquiryuk@fosroc.com

**EMERGENCY TELEPHONE** 01827 265279

### 2 HAZARDS IDENTIFICATION

Repeated exposure may cause skin dryness or cracking. May cause harm to breastfed babies. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**CLASSIFICATION (1999/45)** N;R50/53. R64, R66.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %	Classification (67/548/EEC)
CHLORINATED PARAFFIN (C14-17)	287-477-0	085535-85-9	10-30%	N;R50/53. R64,R66.
ALKANES, C10-C13, CHLORO	287-476-5	85535-84-8	< 1%	Carc. Cat. 3;R40 R66 N;R50/53
QUARTZ (CRYSTALLINE SILICA)		14808-60-7	< 1%	Xi;R36.

The Full Text for all R-Phrases is Displayed in Section 16

### 4 FIRST-AID MEASURES

#### **INHALATION**

Move into fresh air and keep at rest. Perform artificial respiration if breathing has stopped. Get medical attention.

#### **INGESTION**

If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Avoid vomiting and normal rinse of stomach because of risk of aspiration. Never give liquid to an unconscious person. Get medical attention if any discomfort continues.

#### **SKIN CONTACT**

Wash skin thoroughly with soap and water. Continue to rinse for at least 15 minutes. Remove contaminated clothing. Get medical attention promptly if symptoms occur after washing.

#### **EYE CONTACT**

Continue to rinse for at least 15 minutes and get medical attention.

### 5 FIRE-FIGHTING MEASURES

#### **EXTINGUISHING MEDIA**

Foam, carbon dioxide or dry powder.

#### **SPECIAL FIRE FIGHTING PROCEDURES**

Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Do not use water jet as an extinguisher, as this will spread the fire.

#### **PROTECTIVE MEASURES IN FIRE**

Self contained breathing apparatus and full protective clothing must be worn in case of fire. Avoid inhalation of vapours/spray and contact with skin and eyes.

### 6 ACCIDENTAL RELEASE MEASURES

#### **PERSONAL PRECAUTIONS**

Avoid inhalation of vapours and contact with skin and eyes.

## COLPOR 200PF BASE

### ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

### SPILL CLEAN UP METHODS

Collect with absorbent, non-combustible material into suitable containers.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Do not use in confined spaces without adequate ventilation and/or respirator. Do not eat, drink or smoke when using the product. Wash at the end of each work shift and before eating, smoking and using the toilet.

### STORAGE PRECAUTIONS

Store in accordance with local regulations. Keep separate from food, feedstuffs, fertilisers and other sensitive material.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
ALUMINOSILICATE ZEOLITE A	MEL	10 mg/m3 Inhal. Dust	4 mg/m3 Resp. Dust			
CALCIUM CARBONATE (STEARATE COATED)	WEL	10 mg/m3 Inhal. Dust	4 mg/m3 Resp. Dust			
QUARTZ (CRYSTALLINE SILICA)	WEL		0,1 mg/m3			
SILICA (HYDROPHOBIC)	WEL	4 mg/m3 Inhal. Dust	10 mg/m3 Resp. Dust			

WEL = Workplace Exposure Limit.

### PROTECTIVE EQUIPMENT



### ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

### RESPIRATORY EQUIPMENT

In case of insufficient ventilation, wear suitable respiratory equipment.

EN405/EN141 (Type A).

### HAND PROTECTION

Chemical resistant gloves required for prolonged or repeated contact.

### EYE PROTECTION

Use safety goggles and face shield in case of splash risk.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

Liquid

## 10 STABILITY AND REACTIVITY

## 11 TOXICOLOGICAL INFORMATION

## 12 ECOLOGICAL INFORMATION

## 13 DISPOSAL CONSIDERATIONS

## 14 TRANSPORT INFORMATION

## 15 REGULATORY INFORMATION

### LABELLING

**COLPOR 200PF BASE**



Dangerous for the environment

**RISK PHRASES**

R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R64	May cause harm to breastfed babies.
R66	Repeated exposure may cause skin dryness or cracking.

**SAFETY PHRASES**

S37	Wear suitable gloves.
S57	Use appropriate containment to avoid environmental contamination.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.

**16 OTHER INFORMATION**

**REVISION DATE**                      20/03/2012

**RISK PHRASES IN FULL**

R36	Irritating to eyes.
R40	Limited evidence of a carcinogenic effect.
R64	May cause harm to breastfed babies.
R66	Repeated exposure may cause skin dryness or cracking.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.