

#### SAFETY DATA SHEET

## Sikacem 133 Gunite

Date of issue - 30/01/2004. SIKC13

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product Code SIKC13

Product Name Sikacem 133 Gunite

Product Description Single component polymer modified cementitious repair mortar for

concrete.

Manufacturer/Supplier Sika Limited

Watchmead

Welwyn Garden City Hertfordshire. AL7 1BQ tel. 01707 394444

tel. 01707 394444 Fax. 01707 329129

### 2. COMPOSITION/INFORMATION ON THE COMPONENTS

Preparation - Hazardous ingredients ( Europe )

 Component
 CAS/EINECS
 Concentration
 Classification
 Risk Phrases

 Portland Cement
 65997-15-1
 25.00% - 50.00%
 Xi
 R41

 Limestone
 1317-65-3
 50.00% - 100.00%

 Silica,amorphous
 7631-86-9
 2.50% - 10.00%

### 3. HAZARD IDENTIFICATION

Main Hazards Risk of serious damage to eyes.

Dry cement powders in normal use have no harmful effect on the dry skin However when cement is mixed with water or becomes

damp, alkalies are released which can be harmful. Contact with wet cement or wet mortar may cause

irritation, dermatitis or burns.

### 4. FIRST AID MEASURES

Eye Contact Immediately flood the eye with plenty of water for at least 15

minutes, holding the eye open. Obtain medical attention urgently.

Skin Contact Wash skin thoroughly with soap and water.

Obtain medical attention if blistering occurs or redness persists. Contaminated clothing should be washed or dry-cleaned before

re-use.

Ingestion Do not induce vomiting. Wash out mouth with water.

*Inhalation* Remove from exposure.

In cases of possible respiratory irritation or if feeling unwell in cases of prolonged exposure, obtain medical attention.

5. FIRE FIGHTING MEASURES

Extinguishing Media Not combustible.

Select extinguishing agent appropriate to other materials involved.

CM Version - 2 Page: 1/4



# SAFETY DATA SHEET Sikacem 133 Gunite

Date of issue - 30/01/2004. SIKC13

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions**Wear appropriate protective clothing.

**Spillages** Avoid creating a dust.

Sweep up into suitable containers for recovery or disposal.

### 7. HANDLING AND STORAGE

**Handling** Avoid inhaling dust.

Exposure by inhalation or skin contact should be minimised by

good Industrial Hygenie practices. Use in well ventilated area.

Storage area should be: cool. dry.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits - GB** 

Portland Cement

UK EH40: OES 10 mg/m3 8h TWA. Dust, total inhalable:
UK EH40: OES 4 mg/m3 8h TWA. Dust, respirable:

UK EH40:OES 10 mg/m3 8hr TWA, total inhalable dust
UK EH40:OES 10 mg/m3 8hr TWA, respirable dust
UK EH40:OES 4 mg/m3 8hr TWA, respirable dust
UK EH40: OES 6 mg/m3 8h TWA. Dust, total inhalable:
UK EH40: OES 2.4 mg/m3 8h TWA. Dust, respirable:

Engineering Control Measures Use of the basic principles of Industrial Hygiene will enable this

material to be used safely.

Every effort should be made to prevent airborne dusts arising

during mixing operations.

Respiratory Protection If limits are exceeded use an approved dust mask.

**Hand Protection** Wear suitable impervious gloves.

Eye Protection Dust tight goggles.

**Body Protection** Protective clothing should be worn which ensures that

cementitious materials do not come into contact with the skin.

Particular care should be taken to ensure that wet mortar does not

enter boots/footwear.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical StatePowder.ColorLight Grey.OdorNone.

pH Approx. 12 in water.
 Solubility - Water Partially soluble.
 Density (kg/m3) Approx. 1600 (loose)

### 10. STABILITY AND REACTIVITY

**Stability** Stable under normal conditions.

Materials to avoid Strong mineral acids.

Hazardous Decomposition Products None known.

CM Version - 2 Page: 2/4



# SAFETY DATA SHEET Sikacem 133 Gunite

Date of issue - 30/01/2004. SIKC13

11. TOXICOLOGICAL INFORMATION

Acute toxicity Low order of acute toxicity.

**Eye irritation** Cement is a severe eye irritant.

Gross exposures or untreated mild exposures can lead to chemical

burning and ulceration of the eye.

Skin irritation Cement and/or water/cement mixtures may cause irritant contact

dermatitis, allergic dermatitis, and/or burns.

12. ECOLOGICAL INFORMATION

Mobility The product is sparingly soluble in water.

Persistence/degradability Inorganic basis,therefore non biodegradable.

Ecotoxicity The alkalinity of this product will have a local effect on ecosystems

sensitive to changes in pH

13. DISPOSAL

Product Disposal Dispose of as Special Waste.

As an inert material it may be disposed of via an approved solid

waste disposal facility.

Container Disposal Empty packaging may be disposed along with normal builders

waste via an authorised waste contractor.

14. TRANSPORT INFORMATION

ADR/RID : Proper shipping name

IMDG : Proper shipping name

Not Regulated under ADR/RID

Not Regulated under IMDG

Not Regulated under IMDG

Not Regulated under IMDG

15. REGULATORY INFORMATION

Label Requirements Irritant

X

**Risk Phrases** Risk of serious damage to eyes.

Safety Phrases In case of contact with eyes, rinse immediately with plenty of water

and seek medical advice. Wear eye/face protection.

**16. OTHER INFORMATION** 

First Issue Date 13.09.1995

Revisions Highlighted Composition / information on ingredients

Exposure controls/personal protection

Regulatory Information

Disposal.

Uses and Restrictions Customers are urged to ensure that the product is entirely suitable

for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by

the use of the product is undertaken.

CM Version - 2 Page: 3/4



# SAFETY DATA SHEET Sikacem 133 Gunite

Date of issue - 30/01/2004.

SIKC13

**UK Legislation** 

**UK Guidance Publications** 

Health and Safety at Work etc Act, 1974, and relevant Statutory

Provisions.

SI 2002/1689: Chemicals (Hazard Information and Packaging)

Regulations

SI 2002/2677: The Control of Substances Hazardous to Health

Regulations

SI No 2839 1991 Environmental Protection (Duty of Care)

Regulations.

SI No. 972/1996: The Special Waste Regulations 1996

General Approved Code of Practice to COSHH Regulations, HSE. EH40, Occupational Exposure Limits, HSE. Revised Annually. EH44, Dust in the Workplace: General Principles of Protection,

HSE.

EH26, Occupational Skin Diseases: Health and Safety

Precautions, HSE.

CONIAC Health Hazard Information Sheet No.26 (Cement)

**Footnote** 

The information contained in this SDS corresponds to our level of

knowledge at the time of publication. All warranties are

excluded. Our most current General Sales Conditions shall apply.

Please consult the Technical Data Sheet prior to use.