



# Sikafloor - 1 MetalTop (formerly SuperTop)

Date of issue - 12/08/2003.

SKFLST

#### 1. PRODUCT AND COMPANY IDENTIFICATION

Product Code SKFLST

Product Name Sikafloor - 1 MetalTop (formerly SuperTop)

Product Description Dry Shake Floor Hardener

Manufacturer/Supplier Sika Limited
Watchmead

Welwyn Garden City Hertfordshire.

AL7 1BQ tel. 01707 394444 Fax. 01707 329129

#### 2. COMPOSITION/INFORMATION ON THE COMPONENTS

Preparation - Hazardous ingredients ( Europe )

Component CAS/EINECS Concentration Classification Risk Phrases

Portland Cement 65997-15-1 10.00% - 25.00% Xi R41

#### 3. HAZARD IDENTIFICATION

Main Hazards Risk of serious damage to eyes.

#### 4. FIRST AID MEASURES

Eye Contact Immediately flood the eye with plenty of water for at least 15

minutes, holding the eye open. Obtain medical attention urgently.

Skin Contact Wash skin thoroughly with soap and water.

Obtain medical attention if blistering occurs or redness persists. Contaminated clothing should be washed or dry-cleaned before

e-use.

Ingestion Do not induce vomiting. Wash out mouth with water.

*Inhalation* Remove from exposure.

In cases of possible respiratory irritation or if feeling unwell in

cases of prolonged exposure, obtain medical attention.

#### 5. FIRE FIGHTING MEASURES

Extinguishing Media Not combustible.

Select extinguishing agent appropriate to other materials involved.

### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Wear appropriate protective clothing.

**Spillages** Avoid creating a dust.

Sweep up into suitable containers for recovery or disposal.

CM Version - 1.01 Page: 1/4



# SAFETY DATA SHEET Sikafloor - 1 MetalTop (formerly SuperTop)

Date of issue - 12/08/2003. SKFLST

# 7. HANDLING AND STORAGE

**Handling** Avoid inhaling dust.

Exposure by inhalation or skin contact should be minimised by

good Industrial Hygenie practices.

Use in well ventilated area.

**Storage** Storage area should be: cool. dry.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits - GB** 

Portland Cement UK EH40: OES 10mg/m3 8h TWA. Dust, total inhalable: UK EH40: OES 4mg/m3 8h TWA. Dust, respirable:

material to be used safely.

Every effort should be made to prevent airborne dusts arising

during mixing operations.

**Respiratory Protection** If limits are exceeded use an approved dust mask.

*Hand Protection* Wear suitable impervious gloves.

**Eye Protection** Dust tight goggles.

**Body Protection** Protective clothing should be worn which ensures that

cementitious materials do not come into contact with the skin. Particular care should be taken to ensure that wet mortar does not

enter boots/footwear.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State Granular powder

Color Various
Odor None.

pH Approx. 12 in water.Solubility - Water Partially soluble.

Density (kg/m3) Approx. 2500. (loose bulk)

### 10. STABILITY AND REACTIVITY

**Stability** Stable under normal conditions.

Materials to avoid Strong mineral acids.

Hazardous Decomposition Products None known.

## 11. TOXICOLOGICAL INFORMATION

Acute toxicity Low order of acute toxicity.

**Eye irritation** Cement is a severe eye irritant.

Gross exposures or untreated mild exposures can lead to chemical

burning and ulceration of the eye.

Skin irritation Frequent or prolonged skin contact may cause some local short

term skin irritation.

CM Version - 1.01 Page: 2/4



# SAFETY DATA SHEET Sikafloor - 1 MetalTop (formerly SuperTop)

Date of issue - 12/08/2003. SKFLST

## 12. ECOLOGICAL INFORMATION

MobilityThe product is sparingly soluble in water.Persistence/degradabilityInorganic basis, therefore non biodegradable.EcotoxicityMaybe harmful to aquatic species, due to alkalinity.

### 13. DISPOSAL

Product Disposal Dispose of as Special Waste.

As an inert material it may be disposed of via an approved solid

waste disposal facility.

Container Disposal Empty packaging may be disposed along with normal builders

waste via an authorised waste contractor.

#### 14. TRANSPORT INFORMATION

ADR/RID: Proper shipping name

IMDG: Proper shipping name

Not Regulated under ADR/ RID

Not Regulated under IMDG.

Not Regulated under IMDG.

Not Regulated under ICAO.

#### 15. REGULATORY INFORMATION

Label Requirements Irritant

×

**Risk Phrases** Risk of serious damage to eyes.

Safety Phrases In case of contact with eyes, rinse immediately with plenty of water

and seek medical advice.

Wear suitable protective clothing, gloves and eye/face protection. After contact with skin, wash immediately with plenty of soap and

water

#### 16. OTHER INFORMATION

First Issue Date 28.11.2002

**Revisions Highlighted** Change of trade name

Uses and Restrictions Customers are urged to ensure that the product is entirely suitable

for their own purpose. It is the customer's responsibilty to ensure that a suitable and sufficient assessment of the risks created by

the use of the product is undertaken.

**UK Legislation** Health and Safety at Work etc Act, 1974, and relevant Statutory

Provisions.

SI 2002/1689: Chemicals (Hazard Information and Packaging)

Regulations,

SI 2002/2677: The Control of Substances Hazardous to Health

Regulations

SI No 2839 1991 Environmental Protection (Duty of Care)

Regulations.

SI No. 972/1996: The Special Waste Regulations 1996

CM Version - 1.01 Page: 3/4



# SAFETY DATA SHEET Sikafloor - 1 MetalTop (formerly SuperTop)

Date of issue - 12/08/2003.

**SKFLST** 

**UK Guidance Publications** 

General Approved Code of Practice to COSHH Regulations, HSE. EH40, Occupational Exposure Limits, HSE. Revised Annually. EH44, Dust in the Workplace: General Principles of Protection, HSE.

EH26, Occupational Skin Diseases: Health and Safety

Precautions, HSE.

CONIAC Health Hazard Information Sheet No.26 (Cement)

**Footnote** 

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.