

Sikafloor - 2 SynTop (formerly Armorshield)

Date of issue - 12/08/2003.

	-
SKFLA	۱S

1. PRODUCT	AND COMPANY	IDENTIFICATION
------------	-------------	----------------

Product Code
Product Name
Product Description
Manufacturer/Supplier

SKFLAS Sikafloor - 2 SynTop (formerly Armorshield) Dry Shake Floor Hardener Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ tel. 01707 394444 Fax. 01707 329129

2. COMPOSITION/INFORMATION ON THE COMPONENTS	

Preparation - Hazardous ingredients (E	urope)			
Component	CAS/EINECS	Concentration	Classification	Risk Phrases
Portland Cement	65997-15-1	10.00% - 25.00%	Xi	R41

3. HAZARD IDENTIFICATION

Main Hazards

Risk of serious damage to eyes.

4. FIRST AID MEASURES	
Eye Contact	Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention urgently.
Skin Contact	Wash skin thoroughly with soap and water. Obtain medical attention if blistering occurs or redness persists. Contaminated clothing should be washed or dry-cleaned before re-use.
Ingestion	Do not induce vomiting. Wash out mouth with water.
Inhalation	Remove from exposure. In cases of possible respiratory irritation or if feeling unwell in cases of prolonged exposure,obtain medical attention.

5. FIRE FIGHTING MEASURES

Extinguishing Media

Not combustible.

Select extinguishing agent appropriate to other materials involved.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Wear appropriate protective clothing.
Spillages	Avoid creating a dust. Sweep up into suitable containers for recovery or disposal.



SAFETY DATA SHEET Sikafloor - 2 SynTop (formerly Armorshield)

Date of issue - 12/08/2003.

SKFLAS

7. HANDLING AND STORAGE

Handling

Storage

Avoid inhaling dust. Exposure by inhalation or skin contact should be minimised by good Industrial Hygenie practices. Use in well ventilated area. Storage area should be: cool. dry.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits - GB	
Portland Cement	UK EH40: OES 10mg/m3 8h TWA. Dust, total inhalable: UK EH40: OES 4mg/m3 8h TWA. Dust, respirable:
Engineering Control Measures Respiratory Protection	Use of the basic principles of Industrial Hygiene will enable this material to be used safely. Every effort should be made to prevent airborne dusts arising during mixing operations. If limits are exceeded use an approved dust mask.
Hand Protection	Wear suitable impervious gloves.
Eye Protection	Dust tight goggles.
Body Protection	Protective clothing should be worn which ensures that cementitious materials do not come into contact with the skin. Particular care should be taken to ensure that wet mortar does not enter boots/footwear.

Physical State	Granular Powder.
Color	Various
Odor	None.
рН	Approx. 12 in water.
Solubility - Water	Partially soluble.
Density (kg/m3)	Approx. 2000. (loose bulk)

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Materials to avoid	Strong mineral acids.
Hazardous Decomposition Products	None known.

11. TOXICOLOGICAL INFORMATION	
Acute toxicity	Low order of acute toxicity.
Eye irritation	Cement is a severe eye irritant. Gross exposures or untreated mild exposures can lead to chemical burning and ulceration of the eye.
Skin irritation	Frequent or prolonged skin contact may cause some local short term skin irritation.



SAFETY DATA SHEET

Sikafloor - 2 SynTop (formerly Armorshield) Date of issue - 12/08/2003.

SKFLAS

Mobility	The product is sparingly soluble in water.
Persistence/degradability	Inorganic basis,therefore non biodegradable.
Ecotoxicity	Maybe harmful to aquatic species, due to alkalinity.
13. DISPOSAL	
Product Disposal	Dispose of as Special Waste. As an inert material it may be disposed of via an approved solid

Container Disposal

waste disposal facility. Empty packaging may be disposed along with normal builders waste via an authorised waste contractor.

ADR/RID : Proper shipping name	Not Regulated under ADR/ RID	
IMDG : Proper shipping name	Not Regulated under IMDG.	
IATA : Proper shipping name	Not Regulated under ICAO.	

15. REGULATORY INFORMATION

Label Requirements

Risk Phrases Safety Phrases



Irritant

Risk of serious damage to eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of soap and water

Wear suitable protective clothing, gloves and eye/face protection.

16. OTHER INFORMATION		
First Issue Date	28.11.2002	
Revisions Highlighted	Change of trade name	
Uses and Restrictions	Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.	
UK Legislation	Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions. SI 2002/1689: Chemicals (Hazard Information and Packaging) Regulations, SI 2002/2677: The Control of Substances Hazardous to Health Regulations SI No 2839 1991 Environmental Protection (Duty of Care) Regulations. SI No. 972/1996: The Special Waste Regulations 1996	



SAFETY DATA SHEET

Sikafloor - 2 SynTop (formerly Armorshield)

Date of issue -	12/08/2003.	SK
		÷.

KFLAS

General Approved Code of Practice to COSHH Regulations, HSE. **UK Guidance Publications** EH40, Occupational Exposure Limits, HSE. Revised Annually. EH44, Dust in the Workplace: General Principles of Protection, HSE. EH26, Occupational Skin Diseases: Health and Safety Precautions, HSE. CONIAC Health Hazard Information Sheet No.26 (Cement) The information contained in this SDS corresponds to our level of knowledge at the time of publication.All warranties are excluded.Our most current General Sales Conditions shall apply.

Please consult the Technical Data Sheet prior to use.

Footnote