

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sikagard®-551 S Elastic Primer**



Revision Date 01.06.2016

Version 2.1

Print Date 01.09.2016

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Trade name : Sikagard®-551 S Elastic Primer

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Product use : Pretreatment agent

**1.3 Details of the supplier of the safety data sheet**

Company : Sika Limited  
Watchmead  
Welwyn Garden City  
Hertfordshire AL7 1BQ  
United Kingdom

Telephone : +44 (0)1707 394444

**1.4 Emergency telephone number**

Emergency telephone number : +44 (0)1707 363899 (available during office hours)

---

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

Type of product : Mixture

**Classification (REGULATION (EC) No 1272/2008)**

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Chronic aquatic toxicity, Category 2	H411: Toxic to aquatic life with long lasting effects.

**2.2 Label elements**

**Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms : 

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

**SAFETY DATA SHEET**  
 according to Regulation (EC) No. 1907/2006  
**Sikagard®-551 S Elastic Primer**



Revision Date 01.06.2016

Version 2.1

Print Date 01.09.2016

	H335	May cause respiratory irritation.
	H336	May cause drowsiness or dizziness.
	H411	Toxic to aquatic life with long lasting effects.
Supplemental Hazard Statements	: EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statements	: <b>Prevention:</b>	
	P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
	P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
	P273	Avoid release to the environment.
	<b>Response:</b>	
	P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P312	Call a POISON CENTER/doctor if you feel unwell.
	P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

- 918-668-5 Hydrocarbons, C9, aromatics

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**Hazardous components**

Chemical name CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Hydrocarbons, C9, aromatics 128601-23-0 918-668-5 265-199-0 01-2119455851-35-XXXX [corresponding group CAS 64742-95-6]	Flam. Liq.3; H226 STOT SE3; H335, H336 Asp. Tox.1; H304 Aquatic Chronic2; H411	>= 50 - <= 100
Substances with a workplace exposure limit :		
1-methoxy-2-propanol 107-98-2 203-539-1 01-2119457435-35-XXXX	Flam. Liq.3; H226 STOT SE3; H336	>= 5 - < 10



For the full text of the H-Statements mentioned in this Section, see Section 16.

---

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Cough  
Respiratory disorder  
Erythema  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects  
  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO<sub>2</sub>), Dry chemical
- Unsuitable extinguishing media : Water, High volume water jet



### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire. Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.



**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling**

- Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
- Other data : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

- Specific use(s) : No data available

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Components with workplace control parameters**

Components	CAS-No.	Value	Control parameters *	Basis *
1-methoxy-2-propanol	107-98-2	TWA	100 ppm 375 mg/m3	GB EH40
		STEL	150 ppm 560 mg/m3	GB EH40

**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
**Sikagard®-551 S Elastic Primer**



Revision Date 01.06.2016

Version 2.1

Print Date 01.09.2016

## 8.2 Exposure controls

### Personal protective equipment

- Eye protection : Safety glasses with side-shields  
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (0,4 mm),  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### Environmental exposure controls

- General advice : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
**Sikagard®-551 S Elastic Primer**



Revision Date 01.06.2016

Version 2.1

Print Date 01.09.2016

Appearance	:	liquid
Colour	:	colourless
Odour	:	hydrocarbon-like
Odour Threshold	:	No data available
Flash point	:	ca. 33 °C
Autoignition temperature	:	270 °C
Lower explosion limit (Vol-%)	:	0,8 %(V)
Upper explosion limit (Vol-%)	:	7 %(V)
Flammability	:	No data available
Oxidizing properties	:	No data available
pH	:	Not applicable
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Vapour pressure	:	4,9996 hPa
Density	:	ca.0,97 g/cm <sup>3</sup> at 20 °C
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Viscosity, dynamic	:	> 250 mPa.s at 20 °C
Viscosity, kinematic	:	> 20,5 mm <sup>2</sup> /s at 40 °C
Relative vapour density	:	No data available
Evaporation rate	:	No data available

**9.2 Other information**

No data available

---

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sikagard®-551 S Elastic Primer**



Revision Date 01.06.2016

Version 2.1

Print Date 01.09.2016

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

#### Components:

##### Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

##### 1-methoxy-2-propanol:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50: 7,5 mg/l  
Exposure time: 4 h

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

#### Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

#### Product:

Remarks: Repeated exposure may cause skin dryness or cracking.

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Product:

Remarks: No data available



SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sikagard®-551 S Elastic Primer**



Revision Date 01.06.2016

Version 2.1

Print Date 01.09.2016

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.  
Respiratory sensitisation: Not classified based on available information.

**Product:**

Remarks: No data available

**Germ cell mutagenicity**

Not classified based on available information.

**Product:**

Germ cell mutagenicity- Assessment : No data available

**Carcinogenicity**

Not classified based on available information.

**Product:**

Carcinogenicity - Assessment : No data available

**Reproductive toxicity**

Not classified based on available information.

**Product:**

Reproductive toxicity - Assessment : No data available

No data available

**STOT - single exposure**

May cause respiratory irritation.  
May cause drowsiness or dizziness.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

---

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Components:**

**Hydrocarbons, C9, aromatics :**

Toxicity to algae : 2,6 - 2,9 mg/l, 72 h, Pseudokirchneriella subcapitata (green)

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sikagard®-551 S Elastic Primer**



Revision Date 01.06.2016

Version 2.1

Print Date 01.09.2016

algae)

**1-methoxy-2-propanol :**

Toxicity to fish : LC50: > 100 mg/l, 96 h, Fish

Toxicity to daphnia and other aquatic invertebrates : EC50: > 100 mg/l, 48 h, Daphnia (water flea)

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

**12.6 Other adverse effects**

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

---

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sikagard®-551 S Elastic Primer**



Revision Date 01.06.2016

Version 2.1

Print Date 01.09.2016

- European Waste Catalogue : 08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances
- Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

---

## SECTION 14: Transport information

### ADR

- 14.1 UN number** : 1263  
**14.2 Description of the goods** : PAINT  
**14.3 Class** : 3  
**14.4 Packing group** : III  
Classification Code : F1  
Labels : 3  
Tunnel restriction code : (D/E)  
**14.5 Environmentally hazardous** : yes

### IATA

- 14.1 UN number** : 1263  
**14.2 Description of the goods** : Paint  
**14.3 Class** : 3  
**14.4 Packing group** : III  
Labels : 3  
**14.5 Environmentally hazardous** : yes

### IMDG

- 14.1 UN number** : 1263  
**14.2 Description of the goods** : PAINT  
(naphtha (petroleum))  
**14.3 Class** : 3  
**14.4 Packing group** : III  
Labels : 3  
EmS Number 1 : F-E  
EmS Number 2 : S-E  
**14.5 Marine pollutant** : yes

### 14.6 Special precautions for user

No data available

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable



---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Banned and/or restricted (2-methoxypropanol)

REACH Information: All substances contained in our Products are  
- preregistered or registered by our upstream suppliers, and/or  
- preregistered or registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P5c	FLAMMABLE LIQUIDS	5.000 t	50.000 t
E2	ENVIRONMENTAL HAZARDS	200 t	500 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils	2.500 t	25.000 t

VOC-CH (VOCV) : 77,48 %

VOC-EU (solvent) : 77,48 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002  
Control of Substances Hazardous to Health Regulations 2002  
The Management of Health and Safety at Work Regulations 1999  
Health and Safety at Work Act 1974  
Environmental Protection Act 1990 & Subsidiary Regulations

### 15.2 Chemical safety assessment



This product contains substances for which Chemical Safety Assessments are still required.

---

## SECTION 16: Other information

### Full text of H-Statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Aquatic Chronic	Chronic aquatic toxicity
Asp. Tox.	Aspiration hazard
Flam. Liq.	Flammable liquids
STOT SE	Specific target organ toxicity - single exposure
ADR	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	Chemical Abstracts Service
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
IATA	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative and toxic
PNEC	Predicted no effect concentration
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sikagard®-551 S Elastic Primer**



Revision Date 01.06.2016

Version 2.1

Print Date 01.09.2016

---