



## MATERIAL SAFETY DATA

EDITION: 4 DATE: February 2007

### 1. PRODUCT

NAME: **weber.cote EC** (MULSICOAT ELASTOMERIC COATING)

#### Chemical Nature

A high build surface coating based on an aqueous acrylic polymer dispersion available in a range of colours.

#### Manufacturer

##### **Weber**

Saint-Gobain Weber Limited  
Dickens House  
Enterprise Way  
Flitwick  
Bedford.  
MK45 5BY.

EMERGENCY TELEPHONE NUMBER. 08703 330070

### 2. COMPOSITION

An aqueous acrylic polymer dispersion coating containing pigments, fillers and other special additives.

### 3. HAZARDS IDENTIFICATION

Essentially non hazardous according to 88/379/EEC.  
Slightly irritating to eyes and skin

### 4. FIRST AID MEASURES

SKIN CONTACT: Wash off with plenty of soap and water. Do not use organic solvents.

EYE CONTACT: Immediately rinse with water. Seek medical if irritation persists

INHALATION: Move affected person to fresh air.

INGESTION: There is no serious hazard. Rinse mouth with water. If swallowing has occurred the affected person should drink plenty of water. Seek medical attention.

## 5. FIRE FIGHTING MEASURES

The wet material will not burn. Dried films are combustible. Water, foam, carbon dioxide or dry powder extinguishers are all suitable.

### Exposure hazards

Do not release chemically contaminated water into drains, soil or surface water. Sufficient measures must be taken to retain water used for extinguishing. Dispose of contaminated water and soil according to local regulations.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions

Avoid contact with skin, eyes and clothing.

### Environmental Precautions

Prevent contamination of soil drains and surface water.

### Methods for Cleaning

Take up with absorbent, dry inert material (e.g. sand) and place in a suitable and closable container for disposal according to local regulations.

## 7. HANDLING AND STORAGE

### Handling

Mulsicoat Elastomeric Coating should be handled in accordance with good industrial safety and hygiene practices.

### Storage

Store in original undamaged containers securely closed. Store at room temperature away from direct sunlight. Protect from frost.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Technical Protective Measures

No special measures required

### Exposure Limits

None

### Respiratory Protection

Not necessary. Work in well ventilated area.

### Hand Protection

Wear suitable gloves.

### Eye Protection

Wear suitable goggles or face protection

### Skin Protection

Wear overalls

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance: A thixotropic liquid available in a range of colours.  
Odour: Slight characteristic smell of acrylic resin.

**10. STABILITY AND REACTIVITY**

Mulsicoat Elastomeric Coating is stable under normal conditions of use.

**11. TOXICOLOGICAL INFORMATION**

Long-term experience of handling this type of coating under industrial conditions indicates the absence of any chronic or acute effects.

**12. ECOLOGICAL INFORMATION**

Mulsicoat Elastomeric Coating is totally miscible with water. Prevent contamination of soil, drains or surface water. No other specific information available.

**13. DISPOSAL CONSIDERATIONS**

Mulsicoat Elastomeric Coating is not classified as hazardous waste, but residues should not be discharged to drains without prior consent. Existing local regulations must always be complied with.

**14. TRANSPORT INFORMATION**

Mulsicoat Elastomeric Coating is not classified as hazardous for transportation.

**15. REGULATORY INFORMATION**

EC Hazard Classification: None

**16. OTHER INFORMATION**

None

This safety sheet has been prepared in accordance with the provisions of the EC SDS Directive 91/155.